

## HEATER SUBMITTAL SHEET

## DR SERIES HIGH INTENSITY HEATERS

## GAS-FIRED, HIGH INTENSITY, LUMINOUS INFRARED HEATERS &amp; ACCESSORIES

Submitted By: _____	Date: _____
Local Representative: _____	Name: _____
Phone: _____	Email: _____
Notes: _____	
_____	
Engineer: _____	Contractor: _____
Project Title: _____	Phone: _____
Address: _____	Address: _____
City: _____	City: _____
State: _____ Zip: _____	State: _____ Zip: _____

QTY.	MODEL #	TAG	INPUT BTU/h (Indicate Gas Type)		CERAMIC OPERATING TEMP.	SQ. IN. of RADIATING SURFACE	TYP. OR RCMD. MOUNTING HEIGHTS (Standard Reflector)	CONTROL VOLTAGE (See Page 2)			
			NATURAL GAS	PROPANE GAS				NET WEIGHT	— DIRECT SPARK — 120V 24V	Millivolt	
	<b>DR 30</b>		30,000	30,000	1780° F	85	12' to 14'	18 lbs.			
	<b>DR 30(S)</b>		30,000	30,000	1780° F	85	12' to 14'	18 lbs.			
	<b>DR 45</b>		45,000	45,000	1660° F	170	12' to 14'	27 lbs.			
	<b>DR 50</b>		50,000	50,000	1690° F	170	12' to 14'	27 lbs.			
	<b>DR 55</b>		55,000	55,000	1740° F	170	13' to 15'	27 lbs.			
	<b>DR 60</b>		60,000	60,000	1780° F	170	14' to 16'	27 lbs.			
	<b>DR 75</b>		75,000	75,000	1690° F	255	15' to 17'	36 lbs.			
	<b>DR 80</b>		80,000	80,000	1720° F	255	15' to 17'	36 lbs.			
	<b>DR 85</b>		85,000	85,000	1750° F	255	16' to 18'	36 lbs.			
	<b>DR 90</b>		90,000	90,000	1780° F	255	16' to 18'	36 lbs.			
	<b>DR 95</b>		95,000	N/A	1800° F	255	17' to 20'	36 lbs.			
	<b>DR 100</b>		100,000	N/A	1810° F	255	17' to 20'	36 lbs.			
	<b>DR 130</b>		130,000	120,000	1810° F	340	21' to 24'	45 lbs.			
	<b>DR 160</b>		160,000	145,000	1810° F	425	24' to 28'	54 lbs.			


**DETROIT RADIANT  
PRODUCTS COMPANY**

Detroit Radiant Products | Phone: (586) 756-0950  
21400 Hoover Rd. | Email: sales@drp-co.com  
Warren, MI 48089 | www.reverberray.com

LSDR-09/21 (DRPC)









