

RE-VERBER-RAY HEATER
SUBMITTAL SHEET

ELX SERIES ELECTRIC HEATERS-60"

SHORT WAVE AND MEDIUM WAVE ELECTRIC INFRARED HEATERS

PROJECT ID: _____	ADDRESS: _____
PROJECT NAME: _____	_____
DATE: _____	CITY: _____ STATE: _____ ZIP: _____
Submitted By: _____	Address: _____
Company: _____	_____
Phone: _____	City: _____
Email: _____	State: _____ Zip: _____
.....	
Engineer: _____	Contractor: _____
Phone/Email: _____	Phone/Email: _____
Address: _____	Address: _____
City: _____	City: _____
State: _____ Zip: _____	State: _____ Zip: _____

CHOOSING AN ELX MODEL

The ELX Series offers a variety of configurable options including housing color, length, voltage, wattage, element quantity, and element type to fit a wide range of applications.

VOLTAGE OPTIONS

The ELX Series is available in several voltages including 208, 240, 277, 480, and 575 V. The voltage available to the space is an important consideration when determining which chassis and element type to select as voltage is directly related to wattage.

CHASSIS OPTIONS

Each application is different, which is why the ELX Series can be customized in a variety of ways, beginning with the chassis. Available in stainless steel or black powder-coated finishes; 24", 33", 46" or 60"; and one, two, or three heating elements.



Stainless Steel



Black Powder-Coat



Single Element



Double Element



Triple Element


**DETROIT RADIANT
PRODUCTS COMPANY**

Detroit Radiant Products | Phone: (586) 756-0950
21400 Hoover Rd. | Email: sales@drp-co.com
Warren, MI 48089 | www.reverberray.com

LSELX60-07/26 (DRPC)

60" LONG MODELS

3,000 to 4,000 Watts

	Model Number	Replacement Lamp	Voltage*	Total Amps	Total Watts	BTU/h
MEDIUM WAVE ELEMENTS	ELXM-60B1-208 ¹ ELXM-60S1-208 ¹	EL-MW-B60-3.0	208	14.42	3,000	10,236
	ELXM-60B1-240 ¹ ELXM-60S1-240 ¹	EL-MW-C60-3.0	240	12.50	3,000	10,236
	ELXM-60B1-277 ¹ ELXM-60S1-277 ¹	EL-MW-D60-3.0	277	10.83	3,000	10,236
HIGH-OUTPUT MEDIUM WAVE ELEMENTS	ELXT-60B1-480 ¹ ELXT-60S1-480 ¹	EL-HO-G60	480	8.33	4,000	13,649
	ELXT-60B1-575 ¹ ELXT-60S1-575 ¹	EL-HO-H60	575	6.96	4,000	13,649

¹ Not available to ship via UPS. Truckline only.

NOTE: Heaters are configured at the factory for single phase wiring. If three phase service is desired, it must be wired as such in the field by a trained installer/electrical contractor.



**DETROIT RADIANT
PRODUCTS COMPANY**

Detroit Radiant Products | Phone: (586) 756-0950
21400 Hoover Rd. | Email: sales@drp-co.com
Warren, MI 48089 | www.reverberray.com

FEATURED SPECIFICATIONS

APPROVALS

- UL Listed
- Indoor & Outdoor Commercial/Industrial Approval
- Outdoor Residential Approval

HEATER CONSTRUCTION (Choose)

- Black powder-coat aluminized steel housing
- 304 brushed stainless steel housing for added durability and corrosion resistance
- High temperature louvered nylon end caps

LAMP ELEMENTS

- Interchangeable standard medium wave, high-output medium wave, & clear or ruby short wave element options
- Coiled tungsten filament housed within a sealed quartz tubing
- Stainless steel end caps
- Instantaneous heat-up and cool-down

ELECTRICAL SUPPLY

- Voltages from 208 to 575 VAC
- Single-phase (can be wired in field as three-phase)
- 3,000 to 4,000 W per element

CONTROLS

- Field supplied

MOUNTING

- 0° to 45° adjustable brackets

REFLECTORS

- Gold-colored, anodized aluminum reflectors reduce visible light glare
- Wide, symmetric design

LIMITED WARRANTY

- 1 year—All components
- Please contact the factory for further information on the terms and conditions.*

OPTIONAL ACCESSORIES

- | | |
|---|--|
| ☐ EL-1FR60 | Black finish recessed mount—fits 60" single element |
| ☐ EL-1FR60-SS | Stainless steel recessed mount—fits 60" single element |
| ☐ EL-WMB | Stainless steel wall mounting brackets. Designed to support heater in a sidewall mounting application. One set per heater. |
| ☐ EL-1WG60 | Stainless steel wire guard—fits 60" single element |



**DETROIT RADIANT
PRODUCTS COMPANY**

Detroit Radiant Products | Phone: (586) 756-0950
21400 Hoover Rd. | Email: sales@drp-co.com
Warren, MI 48089 | www.reverberray.com