RE-VERBER-RAY HEATER SUBMITTAL SHEET

DSCD SERIES PATIO HEATERS

GAS-FIRED, TWO STAGE, HIGH INTENSITY INFRARED PATIO HEATERS & ACCESSORIES

PROJECT ID: _____ ADDRESS: _____

PROJECT NAME: _____ _____

DATE: _____ CITY: _____ STATE: _____ ZIP: _____

Submitted By: _____ Address: _____

Company: _____ _____

Phone: _____ City: _____

Email: _____ State: _____ Zip: _____

Engineer: _____ Contractor: _____

Phone/Email: _____ Phone/Email: _____

Address: _____ Address: _____

City: _____ City: _____

State: _____ Zip: _____ State: _____ Zip: _____

QTY.	MODEL #	TAG	HOUSING[1]	INDICATE GAS TYPE	BTU/h INPUT	SHIP WEIGHT	SHIP WEIGHT W/ PH-BKT	TYP. OR RCMD. MOUNTING HEIGHTS[2]	APPROX. AREA HEATED	CONTROL VOLTAGE
	DSCD-31		Black	Natural Gas or Propane	31,000	28,000	59 lbs.	65 lbs.	8.0' to 12.0'	8' x 8'
	DSCD-34		Black	Natural Gas	34,000	28,000	59 lbs.	65 lbs.	8.5' to 13.0'	9' x 9'
	DSCD-31-SS		Stainless Steel	Natural Gas or Propane	31,000	28,000	59 lbs.	65 lbs.	8.0' to 12.0'	8' x 8'
	DSCD-34-SS		Stainless Steel	Natural Gas	34,000	28,000	59 lbs.	65 lbs.	8.5' to 13.0'	9' x 9'

[1]Black= Black powder-coated aluminized steel

[2]Typical or recommended mounting heights are provided as a guideline. Actual conditions may dictate variations from this data.

DETROIT RADIANT PRODUCTS COMPANY

Detroit Radiant Products
21400 Hoover Rd.
Warren, MI 48089

Phone: (586) 756-0950
Email: sales@drp-co.com
www.reverberray.com

DSCD SERIES FEATURED SPECIFICATIONS

APPROVALS
- ETL Certified
- Commercial/Industrial/ Residential Outdoor Approval

NOMINAL MANIFOLD PRESSURE
- Natural Gas - 6.0 in. W.C.
- Propane Gas - 10.0 in. W.C.

MINIMUM HEATER INLET PRESSURE
- Natural Gas - 7.0 in. W.C.
- Propane Gas - 11.0 in. W.C.

MAXIMUM INLET PRESSURE
- ½ lb. or 14.0 in. W.C.

INLET PIPE SIZE
- ½" NPT

ELECTRICAL REQUIREMENT
- 24VAC with a NEC Class 2 transformer (field supplied)

AMP DRAW 24 VAC/20 VA
- 0.61 Amp starting
- 0.55 Amp running

MOUNTING
- 0° to 30° from horizontal
- Optional - Mounting Brackets (PH-BKT(-SS)) preset mounting angles and height adjustment

CONTROLS
- Two-stage (24 V)
- Switching device
- Timer device

EXTERIOR HOUSING FINISH
- Black coated aluminized steel
- Brushed stainless steel

LIMITED WARRANTY
- 5 years - Ceramic burner
- 1 year - All components

OPTIONAL ACCESSORIES

☐	**PH-BKT**	Adjustable mounting bracket (black powder-coated). Preset 0–30° adjustable wall/ceiling mounting kit.
☐	**PH-BKT-SS**	Adjustable mounting bracket (stainless steel). Preset 0–30° adjustable wall/ceiling mounting kit.
☐	**TR-96VA**	96 VA transformer. Connect up to five (5) DSC Series heaters per transformer.
☐	**PLQ**	Clearance warning plaque. Restates clearances to combustibles warning.

DETROIT RADIANT PRODUCTS COMPANY
Detroit Radiant Products
21400 Hoover Rd.
Warren, MI 48089
Phone: (586) 756-0950
Email: sales@drp-co.com
www.reverberray.com